



Model Name	<b>VT-156JTx7</b>
Description	
<b>Product Type</b>	True Flat Series Plastic Medical LCD monitor
<b>Chassis Type</b>	Plastic chassis ( ABS ) with 100 x 100 mm VESA mount
<b>DICOM / GAMMA</b>	Optional: Gamma 2.2 / DICOM
<b>Glass / Touch Panel</b>	Optional: Projective capacitive touch (USB interface) / Glass
<b>LCD Panel Spec</b>	15.6" LED backlight
<b>Panel Resolution</b>	1920 x 1080 pixels
<b>Active Screen Area</b>	344.16 x 193.59 mm
<b>Color Depth</b>	16.2M colors (RGB 6-bits+FRC)
<b>Brightness / Contrast</b>	500 nits / 1000 :1
<b>Viewing Angle (Typ.)</b>	178°(H) / 178°(V)
<b>Support Resolution</b>	640 x 480 800 x 600

	<p>1024 x 768</p> <p>1280 x 1024</p> <p>1360 x 768</p> <p>1680 x 1050</p> <p>1920 x 1080</p>
<b>I/O Port</b>	<p>DVI</p> <p>DP 1.2</p> <p>HDMI 1.4</p> <p>Audio in (3.5mm Phone Jack)</p> <p>USB 2.0 Type B (Touch)(Optional)</p> <p>DC Jack ( <math>\phi = 2.5\text{mm}</math> ) (Lockable)</p>
<b>Audio</b>	Optional: 2.5W ( 8 $\Omega$ ) speaker x 2
<b>Power</b>	External power adapter, AC IN: 100 ~ 240V ; DC OUT: 12V / 5A
<b>Power Consumption</b>	Max. 19.8 W
<b>Accessory (Optional)</b>	<p>DVI cable</p> <p>HDMI cable</p> <p>DP cable</p> <p>Audio cable</p> <p>USB cable</p> <p>Adapter</p> <p>Power cable, CD</p>
<b>Dimension</b>	Main body :392.96(W) 326.73(H) 159.96(D) mm
	Packing : 508(W) 394(H) 196(D) mm

<b>Net Weight</b> (Reference)	4.1 kg
<b>Gross Weight</b> (Reference)	6.0 kg
<b>Temperature Range</b>	Operating : 5 ~ 40°C / Storage : -10 ~ 60°C
<b>Humidity Range</b>	Operating : 20 ~ 80% / Storage : 10 ~ 90%
<b>EMC / Safety</b>	IEC60601 / CE / FCC, RoHS / REACH

