



Model Name	VT-215XTx3	VT-215XTx4	VT-215DTx3	VT-215DTx4
Description				
Product Type	True Flat Series Plastic LCD monitor			
Chassis Type	Plastic chassis (ABS) with 100 x 100 mm VESA mount			
Enhanced Chassis	N/A			
Glass / Touch Panel	Optional: Projective capacitive touch (USB interface) / Glass			
LCD Panel Spec	21.5" LED backlight			
Panel Resolution	1920 x 1080 pixels			
Active Screen Area	476.064 x 267.786 mm			
Color Depth	16.7M colors			
Brightness / Contrast	250 nits / 1000 :1			
Viewing Angle (Typ.)	178°(H) / 178°(V)			
Support Resolution	640 x 480 800 x 600			

	1024 x 768 1280 x 1024 1360 x 768 1680 x 1050 1920 x 1080			
I/O Port	D-Sub (VGA) DP 1.2 HDMI 1.4a Audio in(3.5mm Phone Jack) USB 2.0 Type B (Touch)(Optional) DC Jack ($\phi = 2.0\text{mm}$)	D-Sub (VGA) DP 1.2 HDMI 1.4a Audio in(3.5mm Phone Jack) USB 2.0 Type B (Touch)(Optional) AC Socket	D-Sub (VGA) DVI Audio in(3.5mm Phone Jack) USB 2.0 Type B (Touch)(Optional) DC Jack ($\phi = 2.0\text{mm}$)	D-Sub (VGA) DVI Audio in(3.5mm Phone Jack) USB 2.0 Type B (Touch)(Optional) AC Socket
Audio	Optional: 2.5W (8 Ω) speaker x 2			
Power	External power adapter, AC IN: 100 ~ 240V ;50/60Hz DC OUT: 12V / 5A	Internal power adapter, AC IN: 100 ~ 240V ;50/60Hz	External power adapter, AC IN: 100 ~ 240V ;50/60Hz DC OUT: 12V / 5A	Internal power adapter, AC IN: 100 ~ 40V ;50/60Hz
Power Consumption	Max. 19.1 W			
Accessory (Optional)	VGA cable DP cable HDMI cable Audio cable USB cable Adapter	VGA cable DP cable HDMI cable Audio cable USB cable Power cable, CD	VGA cable DVI cable Audio cable USB cable Adapter Power cable, CD	VGA cable DVI cable Audio cable USB cable Power cable, CD

	Power cable, CD
Dimension	Main body : 525.3(W) 378(H) 180(D) mm
	Packing : 575(W) 475(H) 259(D) mm
Net Weight (Reference)	5.9 kg
Gross Weight (Reference)	7.5 kg
Temperature Range	Operating : 5 ~ 40°C / Storage : -10 ~ 60°C
Humidity Range	Operating : 20 ~ 80% / Storage : 10 ~ 90%
EMC / Safety	IEC62368 / CE / FCC, RoHS / REACH

