


Description	Model Name	VT-215JT _x 7
Product Type	True Flat Series Plastic Medical LCD monitor	
Chassis Type	Plastic chassis (ABS) with 100 x 100 mm VESA mount	
DICOM / GAMMA	Optional: Gamma 2.2 / DICOM	
Glass / Touch Panel	Optional: Projective capacitive touch (USB interface) / Glass	
LCD Panel Spec	21.5" LED backlight	
Panel Resolution	1920 x 1080 pixels	
Active Screen Area	476.064 x 267.786 mm	
Color Depth	16.7M colors	
Brightness / Contrast	350 nits / 1000 :1	
Viewing Angle (Typ.)	178°(H) / 178°(V)	
Support Resolution	640 x 480 800 x 600	

	<p>1024 x 768</p> <p>1280 x 1024</p> <p>1360 x 768</p> <p>1680 x 1050</p> <p>1920 x 1080</p>
I/O Port	<p>DVI</p> <p>DP 1.2</p> <p>HDMI 1.4</p> <p>Audio in(3.5mm Phone Jack)</p> <p>USB 2.0 Type B(Touch)(Optional)</p> <p>DC Jack ($\phi = 2.5\text{mm}$)(lockable)</p>
Audio	Optional : 2.5W (8 Ω) speaker x 2
Power	External power adapter, AC IN: 100 ~ 240V ; DC OUT: 12V / 5A
Power Consumption	Max. 22.3 W
Accessory (Optional)	<p>DVI cable</p> <p>HDMI cable</p> <p>DP cable</p> <p>Audio cable</p> <p>USB cable</p> <p>Adapter</p> <p>Power cable, CD</p>
Dimension	Main body : 525.3(W) 378(H) 180(D) mm

	Packing : 575(W) 475(H) 259(D) mm
Net Weight (Reference)	5.9 kg
Gross Weight (Reference)	7.0 kg
Temperature Range	Operating : 5 ~ 40°C / Storage : -10 ~ 60°C
Humidity Range	Operating : 20 ~ 80% / Storage : 10 ~ 90%
EMC / Safety	IEC60601 / CE / FCC, RoHS / REACH



UNLESS OTHERWISE SPECIFIED	
LENGTH	TOLERANCE
0-6	±0.10
7-30	±0.15
31-100	±0.20
101-300	±0.25
301-UP	±0.30
ANGLE	±1.0°

TITLE	VT-215JTP7	DATE	2023/5/29	MATERIAL THICKNESS	--		UNIT	mm	CHECK	Kevin	SHEET	1/1	宜奇企業股份有限公司 VITA ELECTRONICS CO., LTD.
P/N	--	REV.	--	FINISH	--		SCALE	1:1	DRAW	Adiley	SIZE	AU 1.5倍	