



| Model Name | VT-150DAx1 | VT-150XAx1 | VT-150VAN1 | VT-150RAN1 | VT-150NAN1 |
|------------------------------|---|------------|----------------------|------------|------------|
| Description | | | | | |
| Product Type | Plastic LCD monitor | | | | |
| Chassis Type | Plastic chassis (ABS) with 75 x 75 mm VESA mount | | | | |
| Enhanced Chassis | N/A | | | | |
| Glass / Touch Panel | Optional : 5 wire resistive touch module (USB / RS232 interface) | | N/A | | |
| LCD Panel Spec | 15" LED backlight | | | | |
| Panel Resolution | 1024 x 768 pixels | | | | |
| Active Screen Area | 304.1 x 228.1 mm | | 304.128 x 228.096 mm | | |
| Color Depth | 16.2M / 262K colors | | | | |
| Brightness / Contrast | 300 nits / 2000 :1 | | 350 nits / 800 :1 | | |
| Viewing Angle (Typ.) | 176°(H) / 176°(V) | | 160°(H) / 150°(V) | | |
| Support Resolution | 640 x 480 | | | | |

| | | | | | |
|-----------------------------|--|--|--|---|--|
| | 800 x 600 | | | | |
| | 1024 x 768 | | | | |
| I/O Port | D-Sub (VGA) DVI Audio in (3.5mm Phone jack) USB 2.0 Type B (Touch) (Optional) RS232 (Touch) (Optional) DC Jack ($\phi = 2.0\text{mm}$) | D-Sub (VGA) HDMI 1.4a DP 1.2 Audio in (3.5mm Phone jack) USB 2.0 Type B (Touch) (Optional) RS232 (Touch) (Optional) DC Jack ($\phi = 2.0\text{mm}$) | D-Sub (VGA) Audio in (3.5mm Phone jack) DC Jack ($\phi = 2.0\text{mm}$) | D-Sub (VGA) HDMI 1.3a CVBS S-Video in Audio in (3.5mm Phone jack) DC Jack ($\phi = 2.0\text{mm}$) | D-Sub (VGA) HDMI 1.3a BNC in BNC out Audio in (3.5mm Phone jack) DC Jack ($\phi = 2.0\text{mm}$) |
| Audio | Optional : 1W (8 Ω) speaker x 1 | | | | |
| Power | External power adapter, AC IN: 100 ~ 240V ; DC OUT: 12V / 5A | | | | |
| Power Consumption | Max. 15.9 W | | | | |
| Accessory (Optional) | VGA cable DVI cable Audio cable USB cable RS232 cable Adapter | VGA cable HDMI cable DP cable Audio cable USB cable RS232 cable | VGA cable Audio cable Adapter Power cable, CD | VGA cable HDMI cable CVBS cable S-Video cable Audio cable Adapter | VGA cable HDMI cable BNC cable Audio cable Adapter Power cable, CD |

| | | | | | |
|---------------------------------|---|-----------------|--|-----------------|--|
| | Power cable, CD | Adapter | | Power cable, CD | |
| | | Power cable, CD | | | |
| Dimension | Main body :347(W) 327(H) 160(D) mm | | | | |
| | Packing : 430(W) 460(H) 230(D) mm | | | | |
| Net Weight (Reference) | 4.3 kg / 3.4 kg (w/o touch) | | | | |
| Gross Weight (Reference) | 5.2 kg / 4.0 kg (w/o touch) | | | | |
| Temperature Range | Operating : 5 ~ 40°C / Storage : -10 ~ 60°C | | | | |
| Humidity Range | Operating : 20 ~ 80% / Storage : 10 ~ 90% | | | | |
| EMC / Safety | IEC62368 / CE / FCC, RoHS / REACH | | | | |

